

DVI/VGA capture card

Installation instructions

The VGA/DVI capture card set includes:

- 1 x capture card DVI/VGA UFG-03A STD
- 1 x connecting block with DVI/VGA connectors
- 1 x VGA HD 15P M/5XBNC cable *
- 1 x DVI-D M/DVI-D M cable *
- 1 x SVGA HD 15M/HD 15M DDC cable *

* these cables are not necessary for installation of the DVI/VGA card to the fixture. They can be used for connection between DigitalSpot 7000 DT and an external signal source.

Here are instructions for installing the DVI/VGA capture card:

1. Disconnect the DigitalSpot 7000 DT from power.
2. Remove both top covers (1) of the fixture base by unscrewing 14 screws (2).
3. Remove the cover plate (3) of unused slots for DVI/VGA connectors on the rear panel of the fixture by unscrewing 4 screws (4).
4. Screw the connecting block (5) with DVI/VGA connectors to the rear panel by means of the 4 hexagonal pillars which have a threaded stud.
5. Remove the capture card (6) from its packaging and gently press it down into the empty PCI slot. Secure the bracket of the card to the chassis by means of the screw (7) with M3 thread.
6. Connect a VGA and DVI cable to the capture card.
7. Place both top covers of the fixture base back and fasten them by 14 screws.
8. After switching the fixture on, the capture card should be ready for operation.

